

Specifications 12G HD-SDI 101

TRUE 4K specification

Max. 4K Capabilities		
Resolution and Refresh Rate	Chroma Sampling	Max. Bit Depth per Color
4096x2160 at 60 Hz	4:2:2	10 bit
3840x2160 at 60 Hz		
4096x2160 at 30 Hz	4:4:4	12 bit
3840x2160 at 30 Hz		

Frame rate¹ 23.97, 24, 29.97, 30, 50, 59.94 and 60 fps
Chroma sampling¹ 4:4:4, 4:2:2, and 4:2:0
Color bit depth¹ 8 or 10 bits per color
Signal type 6G-SDI, 12G-SDI
Max. video data rate 11.88 Gbps per 12G-SDI connection

NOTE: ¹Subject to the maximum data rate limit. Use our calculator (www.extron.com/8Kdatarate) to determine video parameters supported by this data rate.

Video

Signal type SDI, HD-SDI, 3G-SDI, 6G-SDI, and 12G-SDI digital video
Gain Unity
Resolution 8 or 10 bits, automatic
Operation standards SMPTE 259M-C, SMPTE 292M, SMPTE 424M, SMPTE 372M, SMPTE ST-2081, SMPTE 2082, ITU-RBT.601, ITU-RBT.1120
Auto data rate lock Yes
Latency 14 ns
Level mapping Supports both level A and level B mapping (3G-SDI and 6G-SDI)
Bit depth
 12G-SDI Supports up to 10 bits
 6G-SDI Supports up to 10 bits
 3G-SDI Supports up to 12 bits
 HD-SDI Supports up to 12 bits
 SDI Supports up to 12 bits

Video input

Number/signal type 1 single link SDI, HD-SDI, 3G/6G/12G-SDI digital component video
Connector 1 female BNC
Nominal level 0.8 Vp-p
Minimum/maximum levels 0.5 V to 1 Vp-p with no offset
Impedance 75 ohms
Return loss ≥15 dB @ 5 MHz to 2.97 GHz
DC offset (max. allowable) 5 V
Input coupling AC

Specifications • 12G HD-SDI 101 (Continued)

Input cable equalization.....	Automatic for up to -30 dB of cable loss
12G-SDI.....	70 meters (230 feet)
6G-SDI.....	90 meters (295 feet)
3G-SDI.....	180 meters (590 feet)
HD-SDI.....	240 meters (787 feet)
SDI.....	300 meters (984 feet)

NOTE: Transmission distance varies depending on the signal resolution and on the type of cable, source, and display used in the system.

Video output

Number/signal type.....	1 single link SDI, HD-SDI, 3G/6G/12G-SDI digital component video
Connector.....	1 female BNC
Re-clocking.....	Automatic for 270 Mbps, 1.485 Gbps, 2.97 Gbps, 5.94 Gbps, and 11.88 Gbps (bypassed for all other rates)
Nominal level.....	0.8 Vp-p
Minimum/maximum levels.....	0.5 V to 1.0 Vp-p
Impedance.....	75 ohms
Return loss	>25 dB @ 100 MHz
DC offset	±5 mV with input at 0 offset

Audio

Audio channels	Supports up to 16 channels
----------------------	----------------------------

General

Power supply.....	External Input: 100-240 VAC, 50-60 Hz Output: 12 VDC, 0.5 A, 6 watts
Power input requirements	12 VDC, 0.1 A
Power consumption	
Device	1.0 watts @ 12 VDC
Device and power supply	1.2 watts @ 12 VDC
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Thermal dissipation	
Device	3.2 BTU/hr
Device and power supply	3.8 BTU/hr
Mounting	
Rack mount.....	Yes, with optional rack shelf kit
Enclosure type	Metal
Enclosure dimensions	1.0" H x 2.2" W x 3.0" D (one-eighth rack wide) (2.5 cm H x 5.6 cm W x 7.6 cm D) (Depth excludes connectors.)
Product weight	0.1 lbs (0.1 kg)
Regulatory compliance.....	CE, c-UL, UL, FCC Class A, VCCI, AS/NZS, ICES
Product warranty	3 years parts and labor
Everlast power supply warranty.....	7 years parts and labor

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.