

Specifications

ACP 105 EU Control Panel

ACP Control Interface

| | |
|-----------------------------|--|
| ACP control ports | (2) 3.5 mm captive screw connectors, 4 pole |
| ACP pin configuration | +V = +12 VDC; +S = + signal; -S = - signal; G = ground |
| Recommended cable type..... | Extron STP20-2/1000 or STP20-2P/1000 cable |

Software Configuration

| | |
|----------------|-------------------------|
| Software | Extron DSP Configurator |
|----------------|-------------------------|

General

| | |
|--------------------------------|--|
| Power | Power is supplied by an ACP enabled processor or optional power supply |
| ACP power consumption..... | 1.5 watts, 12 VDC (device only) |
| Temperature/humidity | Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing |
| Cooling | Convection, no vents |
| Thermal dissipation | 3.9 BTU/hr |
| Mounting | |
| Rack mount..... | No |
| Furniture or wall mount..... | Yes, in a standard 1-gang EU electrical junction box |
| Enclosure type | Plastic faceplate, metal mounting plate |
| Enclosure dimensions | |
| Plastic faceplate | 3.2" H x 3.2" W x 0.4" D (8.1 cm x 8.1 cm x 1 cm) |
| Metal mounting plate..... | 2.8" H x 2.8" W x 0.6" D (7.1 cm x 7.1 cm x 1.6 cm) (Fits the opening in a 1-gang EU wallplate) |
| Device..... | 1.8" H x 1.8" W x 0.6" D (4.6 cm x 4.6 cm x 1.6 cm) (Depth excludes faceplate and buttons) |
| Device and captive screw | 1.8" H x 1.8" W x 1" D (4.6 cm x 4.6 cm x 2.6 cm) |
| Product weight | 0.2 lbs (0.1 kg) |
| Regulatory compliance..... | CE, c-UL, C-tick, FCC Class A, ICES, RoHS, UL, VCCI Class A, WEEE, Section 508 of the Rehabilitation Act (29 U.S.C. 964d) |
| Product warranty | 3 years parts and labor |

NOTE: All nominal levels are at $\pm 10\%$.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.

